Porsche

Model	Year	Chassis	Engine	MT	Clutch Type	Spec I					Spee	Price	Note		
						Model #		Clamping	Pedal	Model #		Clamping	Pedal	\$	
spec II is equipped with a new pressure plate and floating plate(s) (for twin/triple					or twin/triple)	model #		Force (kg) Effo				Force (kg) Effort			
	-89.8	930 late model	NA	Censor gear	Triple	CP23H310	-20	2,000		CP23H310	-20	2,000		\$2,374.29	#50
				129 teeth	Twin	CP23H210	-20	2,000		CP23H210	-20	2,000		\$2,074.29	#50
				Censor gear	Triple	CP23H340	-20	2,000		CP23H340	-20	2,000		\$2,374.29	#53
				58 teeth	Twin	CP23H240	-20	2,000		CP23H240	-20	2,000		\$2,074.29	#53
	89	964 Carrera 4	NA	Censor gear	Triple	CP23H340	-20	2,000		CP23H340	-20	2,000		\$2,374.29	#53
				58 teeth	Twin	CP23H240	-20	2,000		CP23H240	-20	2,000		\$2,074.29	#53
	90-	964	NA	G50, G64	Triple	CP23H320	-20	2,000		CP23H320	-20	2,000		\$2,374.29	#51, #52
					Twin	CP23H220	-20	2,000		CP23H220	-20	2,000		\$2,074.29	#51, #52
	94-	993	NA	G50, G64	Triple	CP23H320	-20	2,000		CP23H320	-20	2,000		\$2,374.29	#51, #52
					Twin	CP23H220	-20	2,000		CP23H220	-20	2,000		\$2,074.29	#51, #52
			Turbo	G64	Triple	CP23H320	-20	2,000		CP23H320	-20	2,000		\$2,374.29	#51, #52
					Twin	CP23H220	-20	2,000		CP23H220	-20	2,000		\$2,074.29	#51, #52
	99-	996 GT2, GT3	NA	G50, G64	Triple	CP23H320	-20	2,000		CP23H320	-20	2,000		\$2,374.29	#52
	04-08	997 GT2, GT3			Twin	CP23H220	-20	2,000		CP23H220	-20	2,000		\$2,074.29	#52
			Turbo	G64	Triple	CP23H320	-20	2,000		CP23H320	-20	2,000		\$2,374.29	#52
					Twin	CP23H220	-20	2.000		CP23H220	-20	2.000		\$2.074.29	#52

Note

#50: The application is for the model with the censor gear of 129 teeth. The clutch bearing sleeve for 964RS and the throwout bearing for 964RS, the flywheel bolt for 930 NA late model (93010220600) are required

#51: For 964RS, no additional parts are required #52: If your car is not 964RS, the following four stock parts are required

* throwout bearing for 964RS

* clutch bearing sleeve of r964RS * flywheel bolt for 964RS (parts # 92810215101)

* pilot bearing 6202ZZ

#53: The application is for the model with the censor gear of 58 teeth. The clutch bearing sleeve for 964RS and the throwout bearing for 964RS, the flywheel bolt for 930 NA late model (93010220600) are required

Lotus

Model	Year	Chassis	Engine	MT	Clutch Type	Spec I				Spec	Price	Note			
						Model #		Clamping	Pedal	Model #		Clamping	Pedal	\$	
Spec II is equipp	Bipec II is equipped with a new pressure plate and floating plate(s) lise K18				or twin/triple)	Woder #		Force (kg)	Effort	Woder #		Force (kg)	Effort		
Elise			K18		Single	ML23142	-10	1,000		ML23H142	-16S	1,600		\$1,395.71	#21
Exige					"Pro-spec"	WIL23142	-13	1,300		ML2311142	-22	2,200		ψ1,333.71	#21
			2ZZ-GE		Twin	ML23250	-11	1,100			<u>-14S</u>				#21, #30
						MEZOZOO	-14	1,350		ML23H250	-19	1,900		\$1,711.43	#21, #30
														ψι,/ ΙΙ.+Ο	#21, #30
															#21, #30
					Single	ML23152	-13	1,300			-16S	1,600			#21
					"Pro-spec"	WIL23132	-16	1,600		ML23H152	-22	2,200		\$1,395.71	#21
															#21
			2ZZ-GE		Single	ML23162	-13	1,300			-16S	1,600			#21, #22
			modified		"Pro-spec"	WIL20102	-16	1,600		ML23H162	-22	2,200		\$1,395.71	#21, #22
															#21, #22

Note

#21: Nissan throwout bearing 30502-14601 is required

#22: This application is for the modified 2ZZ engine with the crank of 1ZZ engine for an increased cubic inches

#30: For the 2ZZ engine tuned for higher rev instead of larger torque, choose the single clutch CL23152-13/16 instead of the twin

Alfa Romeo

Model	Year	Chassis	Engine	MT	Clutch Type	Spec I				S	pec		Price	Note	
						Model #		Clamping	Pedal	Model #		Clamping	Pedal	\$	
pec II is equipped with a new pressure plate and floating plate(s) (for twin/triple)								Force (kg)	Effort			Force (kg)	Effort		
Alfa Romeo	96.9-	145	Inline Four	5MT	Single	MA23112	-13	1,300		-1	6S	1,600			#1
	-01.9		Fork		"Pro-spec"	MAZSTIZ	-16	1,600		MA23H112 -	-22	2,200		\$1,495.71	#1
															#1
	92.9-	155	Inline Four	5MT	Single	MA23112	-13	1,300		-1	6 S	1,600			#1
	-98.5		Fork		"Pro-spec"	WAZSTIZ	-16	1,600		MA23H112 -	-22	2,200		\$1,495.71	#1
															#1
	01.10-	147	Inline Four	5MT	Single	MA23122	-13	1,300		-	-16	1,600			#1, #2
					"Pro-spec"	WAZJIZZ	-16	1,600		MA23H122 -	-22	2,200		\$1,695.71	#1, #2
															#1, #2
	98.5-	156	Inline Four	5MT	Single	MA23122	-13	1,300		-	-16	1,600			#1, #2
	-06.4				"Pro-spec"	IVIAZ31ZZ	-16	1,600		MA23H122 -	-22	2,200		\$1,695.71	#1, #2
															#1, #2
	04.7-	GTV	Inline Four	5MT	Single	MA23122	-13	1,300		-	-16	1,600			#1, #2
	-06.4				"Pro-spec"	MAZJIZZ	-16	1,600		MA23H122 -	-22	2,200		\$1,695.71	#1, #2
					-										#1, #2

Note

#1: Nissan throwout bearing 30502-14601 is required

#2: Vehicle with a concentric slave cylinder release bearing When an ATS clutch is installed on the stock mission with release fork mechanism, ATS bearing sleeve (37204-45) and stock clutch fork kit are required